

WALL-MOUNT 12V DC-OUTPUT UPS

UPS 12-7AH



- Rugged, industrial quality
- Conduction/convection cooled - no fan
- Fully protected
- Field-proven design
- Made in North America

This unit is a small UPS with 12VDC output. A built in BCH 060 battery charger module provides 4A current for 3A rated output and for float charging the built-in 7Ah battery. During normal operation, the UPS 12-7AH serves as a power conditioner, blocking surges, spikes and transients while maintaining stable voltage and float-charging the built-in 7AH gel-cell battery. If the AC power fails, the battery powers the load. The unit also has a low battery disconnect circuit to prevent damage to the battery by low discharge during prolonged AC failure. Mounting flanges on the stainless steel case allow for either surface or wall mounting. The use of components with many years of established reliability and generous headroom results in a high demonstrated MTBF. This UPS system is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage

95-264V AC universal
47-63Hz
Input Current: 1.0Arms max.

Input Protection

Inrush current limiting by surgeistor
Varistor S14K275
Battery fuse (internal)
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

2250VDC input to chassis
4300VDC input to output
8mm spacing
500VDC output to chassis

Standards

Designed to meet EN 60950 and related standards

EMI

EN55022 Class B

Switching Frequency

47kHz +/- 2kHz

Output Voltages/Currents

13.6VDC +/-0.1V/3A
Total 50W max. (incl. 1A for charging). The output is floating; either terminal can be grounded

Line/Load Regulation

± 2% combined from zero load to full load

Output Ripple/Noise

Better than 30mVrms or 120mVpp (@20MHz BW) without battery)

Output Overload Protection

Rectangular current limiting with hiccup type short-circuit protection on the charger section
Current Limit: +4.5A +/- 0.5A without battery
Internal fuses:
Battery: 15A fuse
Output: 5A fuse

Output Over-voltage Protection

Second regulator loop set at 15.0V +/- 1V

Low Voltage Disconnect

10.5V +/- 0.5V

Efficiency

Min. 80% at full load

Operating Temperature Range

0 to +50°C for full specification with proper installation
Wider temperature ranges are available as an option

Temperature Drift

0.03% per deg. C over operating

Cooling

Conduction to customer heatsink or chassis and natural convection

Environmental Protection

Basic ruggedizing.
Heavy ruggedizing for mobile applications available as option

MTBF

150,000h at 45°C
Demonstrated MTBF is significantly higher

Indicators

Internal power ON LED for service purposes

Control Input

None

Alarm Outputs

None

Package/Dimensions

Stainless steel case:
157 x 254 x 71mm
(6.2 x 10" x 2.8") including mounting flanges

Weight

4.55 kg (10 lb.) including battery

Connections

Compression type Phoenix terminal block (inside the case).
Cable reliefs for incoming and outgoing cables

RoHS Compliance

Fully compliant

Warranty

Two years subject to application within good engineering practice

Enhancements to these general specifications and customizing can be accommodated upon request. Specifications subject to change.

Designer and manufacturer of quality converters, inverters, UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility.



ABOPULSE ELECTRONICS LTD

110 Walgreen Road
Ottawa, Ontario. K0A 1L0. CANADA
Tel: (613) 836-3511 Fax: (613) 836-7488
E-mail: absopulse@absopulse.com
www.absopulse.com