

450W, Single-output Power Supply with PFC-Input PFC 319 Series

- Electronic power factor correction (PFC)
- Rugged, industrial quality
- Field-proven design
- Adjustable single output
- 450W output power
- Full electronic protection
- N+1 redundancy as an option



The PFC 319 Series AC/DC power supply with factor corrected input delivers up to 450W output power. This field-proven design has a well documented record of reliable operation in very demanding applications. Its rugged construction ensures that it can withstand high levels of shock and vibration. The PFC 319 features low component count and high efficiency. The use of professional quality components and rigorous quality control results in an MTBF exceeding 150,000 hours at 45°C.

SPECIFICATIONS

Input Voltage

Universal 90 ... 264VAC
47 - 63Hz

Input Protection

Inrush current limiting
Varistor
Internal safety fuse
Lower voltage than the specified min. input will not damage the unit

Power Factor

Min. 0.97 at full load for the entire input range. Meets EN61000-3-2

Isolation

2250VDC input to chassis
4300VDC input to output; 8mm spacing
500VDC output to chassis

Standards

Designed to meet EN 60950 and corresponding UL and CSA standards

EMI

EN55022 Class A as minimum

Switching Frequency

50-150KHz Boost section
(dependent on the load)
55 KHz +/-3KHz for the DC/DC
(half-bridge) section

Hold Up Time

Min. 10ms at any input for 5% drop in the output voltage

Output Voltage/Current

12Vdc/37.5A, 24Vdc/18.7A,
48Vdc/9.4A, 54Vdc/8.3A or
125Vdc/3.6A are standard.
Consult factory for other voltages

Redundancy Diode

Optional
Not available for 12V version

Line/Load Regulation

+/- 1% combined from zero load to full load

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple / Noise

Less than 1% peak-to-peak or
0.2% RMS of the output voltage
(20MHz BW)

Output Overload Protection

Rectangular current limiting with short-circuit protection (no hiccup)
Thermal shutdown in case of insufficient cooling (self resetting)

Output Over-voltage Protection

Second regulator loop.
Typically set at 120% of nominal output voltage

Efficiency

Output voltage dependent .
Typically 80% at full load

Operating Temperature Range

0 to +50°C for full specification,
Extended temp. range available

Temperature Drift

0.03% per °C over operating temperature range

Cooling

Conduction to customer heatsink or chassis and natural convection

Environmental Protection

Basic ruggedizing
Full ruggedizing and conformal coating on request

MTBF

150,000 hours @ 45°C
Demonstrated MTBF is significantly higher

Indicators

None

Alarm Output

Optional

Dimensions

F4: 129 x 67 x 351 mm
5.1x 2.6" x 13.8" including terminal block and flanges
Mounting holes are clear.

Weight

2 kg (4.4 lbs)

Connections

12 pole barrier type terminal block with 3/8" spacing

RoHS Compliance

According to requirements

Warranty

Twelve months subject to application within good engineering practice

Enhancements to these general specifications and customizing can be accommodated upon request. Specifications subject to change.

Designer and manufacturer of quality converters, inverters, UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility.



ABSOPULSE ELECTRONICS LTD
110 Walgreen Road
Ottawa, Ontario. K0A 1L0. CANADA
Tel: (613) 836-3511 Fax: (613) 836-7488
E-mail: absopulse@absopulse.com
www.absopulse.com