

2500VA SINE WAVE OUTPUT INVERTER INDUSTRIAL QUALITY CSI 2K5-XX SERIES

- Filtered input
- Modular design
- Sinusoidal output voltage
- 2500VA output power
- Full electronic protection
- Field-proven design topology



Photograph illustrates only one of a number of chassis options. Please see 'dimensions'

The CSI 2K5-XX Series DC/AC Inverter utilizes established design techniques to ensure high reliability. Suitable for a wide range of applications, the CSI 2K5-XX features full electronic protection, high efficiency and low output noise. The built-in fans provide sufficient airflow for operation without de-rating up to 50°C ambient temperature. The output is fully isolated from the input and may either be used in grounded neutral operation (standard) or in floating mode (optional).

SPECIFICATIONS

Input Voltage

24V, 36V, 48V, 125V, 250Vdc
± 15% are standard
Consult factory for other inputs

Input Protection

Internal safety fuse
Inrush current limiting
Reverse polarity protection

Standards

Designed to meet
C22.2 No. 107.1 - 01,
UL 458 and EN60950

EMI

EN 55022 Class A
as a minimum

Output Voltage

115Vac/21.7A continuous
at 60Hz or 400Hz ; or
230Vac/10.9A continuous
at 50Hz with grounded neutral.
Isolated floating output optional
Consult factory for other output
requirements

Output Wave Form

Sinusoidal

Total Harmonic Distortion

Less than 5% at full load

Efficiency

Input voltage dependent
Typically 80% at full load

Line Regulation

Maximum 0.5%

Load Regulation

Maximum ± 6% from no load
to full load. A ± 2% option is
available

Output Protection

Current limiting with short circuit
protection
Thermal shutdown with automatic
recovery in case of continuous
overload or insufficient airflow

Load Crest Factor

Maximum 3.0 at 90% load

Operating Temperature Range

0° C to +50° C. Extended range
available. Consult factory.

Temperature Drift

0.05% per °C over operating
temperature range

Cooling

Built-in fan

Humidity

5 - 95% non-condensing

Environmental protection

Basic ruggedizing

Dimensions

Input <125Vdc
3U x 19" x 18" (H x W x D)
(30 lbs/14kg)
Input ≥125Vdc; output 115Vac:
13.8" x 5.3" x 16.25" (W x H x D)
(26lbs/12kg)
Input ≥125Vdc; output 230Vac:
11.5" x 5.3" x 16.25" (W x H x D)
(22 lbs/10kg)
Other chassis available upon request

Connections

Input/output: Compression-type
terminals

Options:

Output Fail Alarm (Form C)
Remote Inhibit

Warranty: Twelve months subject to application within good engineering practice
Enhancements to these general specifications can be accommodated upon request
Designed to meet common approval requirements. Specifications are subject to change

**Designer and manufacturer of quality converters, inverters, UPS systems, complete rack mount systems
and DC-input fluorescent lamp inverters since 1982. Custom or standard.
Absopulse is a BABT-approved Facility**



ABOPULSE ELECTRONICS LTD
110 Walgreen Road
Ottawa, Ontario. K0A 1L0. CANADA
Tel: (613) 836-3511 Fax: (613) 836-7488
E-mail: absopulse@absopulse.com
www.absopulse.com