

Sine Wave Output Inverters - Low Profile Series







Selection of low-profile, conduction/convection cooled sine wave output inverters CSI 100-XX-FT ...CSI 1000-XX-FT

Generic Specifications

Input Voltages	24Vdc, 36Vdc, 48Vdc, 125Vdc and 250Vdc Other input options on request
Input Range	-15% to +20% of nominal Other options on request
Efficiency	Model dependent, typically 80%
Input Protection	Internal safety fuse, inrush current limiting. Reverse polarity protection
Isolation	<i>For input <60Vdc</i> Input – chassis: 500Vdc <i>For input >60Vdc <125Vdc</i> Input – chassis: 1700Vdc <i>For input >125Vdc</i> Input – chassis: 2400Vdc <i>For all inputs</i> Input – output : 2250Vdc Output – chassis: 2250Vdc
Safety	Designed to meet EN60950
Output Volts	115V and 230V standard. Other options on request
Output Frequency	50Hz, 60Hz & 400Hz standard. Other options on request
Output Power	100 ... 1000W depending on model
Line Regulation	±0.5% over input range
Load Regulation	±6.0% from 10% to 100% load. Better regulation on request
Protection	Current limiting with short circuit protection Self re-setting thermostat for thermal protection
EMI	EMI EN50122 Class A as a minimum
Load crest factor	Maximum 3 at 90% load
Harmonic Distortion	Less than 5% at full load
Operating temp.	0°C to +50°C. Extended temperature ranges available
Temperature Drift	0.05% per °C over operating temperature range
Output alarm	Optional – available upon request
MTBF	Min.180,000 hours at 45°C
Warranty	Twelve months subject to application within good engineering practice

Features

- Rugged design for harsh environments
- Conduction/convection cooling, no fans
- Highly filtered input/output
- Sinusoidal output waveform
- Full electronic protection
- Field-proven topology
- Railway quality versions for EN50155 are also available

Model	Output V/A	Dimensions	Outline of chassis
CSI 100-XX-FT	100	F1 package: 4.43" x 2" x 7.78"	
CSI 150-XX-FT	150	F2 package: 4.43" x 2.25" x 10"	
CSI 200-XX-FT	200	F3 package: 5.2" x 2.43" x 11.4"	
CSI 300-XX-FT	300	FX package: 6" x 2.63" x 13.82"	
CSI 500-XX-FT	500	F20 package: 10" x 2.58" x 13.8"	
CSI 1000-XX-FT	1000	F30 package: 19" x 2.64" x 13.97"	

Example of complete part number:

CSI 500-4E-FT (48Vdc input; 230Vac/50Hz output)

For Railway applications, please refer to Absopulse's Railway and Industrial Inverter Series at www.absopulse.com/sinwav_1.html
Enhancements to these general specifications and customizing can be accommodated upon request.
Designed to meet common approval requirements. Specifications subject to change.



110 Walgreen Road,
Ottawa, Ontario. K0A 1L0.
Tel: (613) 836-3511 Fax: (613) 836-7488
E-mail: absopulse@absopulse.com
www.absopulse.com