

Transportable Battery Charger for Field Applications BCH 300T and BCH 500T Series



- Extremely rugged
- Field-proven design
- Convection cooled - no fan
- Fully protected
- Made in North America

The BCH 300T and BCH 500T Series of battery chargers was designed for extremely heavy-duty applications such as military, transportation, marine, oilfields and industrial plants. The field-proven circuitry provides many years of trouble free operation in the toughest environments. This series provides up to 500W output power.

Since ABSOPULSE is a custom manufacturer, the design can be adapted to any battery voltage required. A range of options including panel-meters, temperature compensation, charge disconnect, timer and alarms are available on request.

SPECIFICATIONS

Input Voltage

115Vac or 230Vac $\pm 15\%$
47 - 63Hz
or 250Vdc
Universal PFC and DC inputs as options

Input Protection

Inrush current limiting
Surge protection
Reverse battery protection
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Input Isolation

2250VDC input to chassis
4300VDC input to output,
8mm spacing
500VDC output to chassis

Standards

Designed to meet IEC950,
CSA 22-2-950 and UL 60950

EMI

Meets EN 55022 Class A as a minimum

Switching Frequency

55kHz +/- 2kHz

Charger Output Voltage

Any voltage up to 400Vdc

Line/Load Regulation

$\pm 1.5\%$ combined from no load to full load

Output Ripple/Noise

Better than 1% of output voltage peak to peak or 0.2% RMS of the output voltage (20MHZ BW)

Overload Protection

Current limiting with short circuit protection

Output Overvoltage Protection

Double regulator loop

Efficiency

Min 80% at full load

Operating Temperature

0 to +50°C
Extended temperature range available

Temperature Drift

0.03% per °C over operating temperature range

Cooling

Natural convection

Environmental Protection

Heavy ruggedizing, conformal coating, waterproof case

MTBF

150,000h at 45°C

Indicators

Charger ON LED

Battery Temperature Compensation

As option

Battery Reverse Polarity Protection

Crossbar diode and breaker

Equalize & Timer

As option on request

Low Battery Disconnect

None

Alarm Output

Charger fail Form C available as option

Dimensions (W x H x D)

Pelican Top Loader Case #1430
430 x 341 x 244 mm
(17" x 13.5 x 9.7")

Weight

Approx 5.9 kg (13 lb) depending on model

Connections

AC-input: IEC 320 receptacle
Output/battery: Circular MIL type connector.
Battery cable provided on request

RoHS Compliance

According to requirements

Warranty

Two years subject to application within good engineering practice.

Enhancements to these general specifications and customizing can be accommodated upon request. Specifications are subject to change.

Designer and manufacturer of quality converters, inverters, UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility



ABOPULSE ELECTRONICS LTD

110 Walgreen Road
Ottawa, Ontario. K0A 1L0. CANADA
Tel: (613) 836-3511 Fax: (613) 836-7488
E-mail: absopulse@absopulse.com
www.absopulse.com