

500W, Rugged, Industrial Quality AC/DC Power Supply with PFC-Input PFC 65F-FT Series



- Electronic power factor correction (PFC)
- Rugged, industrial quality
- Field-proven design
- Full electronic protection
- N+1 redundancy as an option

The PFC 65F series rugged, industrial quality AC/DC power supply with power factor corrected input uses a field proven design to generate 500W output power. It has an excellent track record in numerous heavy-duty applications. Cooling is by built-in fans, with additional conduction via the baseplate. It has full electronic protection. Low component count, large design headroom, and the use of components with established reliability result in a high MTBF. The unit is manufactured at our plant under strict quality control.

SPECIFICATIONS

<p>Input Voltage Universal 95 ... 264Vac 47 - 420Hz</p> <p>Power Factor is min.0.97 at full load for the entire input range. Meets EN61000-3-2</p> <p>Input Protection Inrush current limiting Varistor Internal safety fuse Lower voltage than the specified minimum input will not damage the unit</p> <p>Isolation 2250VDC input to chassis 4300VDC input to output; 8mm spacing 500VDC output to chassis</p> <p>Standards Designed to meet EN 60950 and related standards</p> <p>EMI EN55022 Class A with margins</p> <p>Switching Frequency 50-150KHz for boost section (dependent on the load) 55 KHz +/-3KHz for the DC/DC (half-bridge) section</p> <p>Hold Up Time Min. 10ms at any input for 5% drop in the output voltage</p>	<p>Output Voltage/Current 12V/40A, 24V/20A or 48V/10A standard. Consult factory for other voltages</p> <p>Redundancy Diode On request</p> <p>Line/Load Regulation +/- 1% combined from zero load to full load</p> <p>Dynamic Response Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time</p> <p>Output Ripple / Noise Less than 1% peak-to-peak or 0.2% RMS of the output voltage (20MHZ BW)</p> <p>Output Overload Protection Rectangular current limiting with short-circuit protection (no hiccup) Thermal shutdown in case of insufficient cooling (self resetting)</p> <p>Output Over-voltage Protection Second regulator loop. Typically set at 120% of nominal output voltage</p>	<p>Efficiency Output voltage dependent . Typically 80% at full load</p> <p>Operating Temperature Range 0°C to 50°C cold plate temperature for full specification without derating Extended temperature range available</p> <p>Temperature Drift 0.03% per °C over operating temperature range</p> <p>Cooling Forced air by two built-in fans and conduction to customer heatsink or chassis</p> <p>Environmental Protection Basic ruggedizing Full ruggedizing and conformal coating on request</p> <p>Shock/Vibration IEC 61373 Cat 1 A&B</p> <p>Humidity 5 - 95% non-condensing</p> <p>MTBF 130,000 hours @ 45 °C (fans excluded) Demonstrated MTBF is significantly higher</p>	<p>Indicators None</p> <p>Control Input None</p> <p>Alarm Output None on standard version</p> <p>Package/Dimensions (W x H x L) FF3: 153 x 64 x 300 mm (6.1" x 2.5" x 11.8") including terminal block, flanges and fans Mounting holes are clear</p> <p>Weight 2.3 Kg (5.0 lb)</p> <p>Connections 12 pole barrier type terminal block, 3/8" spacing</p> <p>RoHS Compliance Fully compliant</p> <p>Warranty Two years subject to application within good engineering practice</p>
---	--	---	--

Enhancements to these general specifications and customizing can be accommodated upon request. Specifications subject to change.

Designer and manufacturer of quality converters, inverters, UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved facility.



ABOPULSE ELECTRONICS LTD
110 Walgreen Road
Ottawa, Ontario. K0A 1L0. CANADA
Tel: +1-613-836-3511 Fax: +1-613-836-7488
E-mail: absopulse@absopulse.com
<http://www.absopulse.com>