

100W, Universal Input, Rugged, Industrial Power Supply

MIW 100-FT Series



- Rugged industrial quality
- Single output
- Conduction/convection cooled
- Full electronic protection
- Field-proven design
- Cost optimized

The MIW 100 Series is a rugged, industrial quality AC/DC power supply that uses a field-proven technology to deliver 100W. It is a mature design with a track record in numerous applications. Cooling is by conduction via baseplate to a heatsinking surface and by natural convection. The unit has full electronic protection. Low component count, large design headrooms, and the use of components with established reliability result in a high MTBF. Additional ruggedizing and conformal coating are available for operation in extreme environments. Open versions with 1.5" heatsink block height are also available on request. The MIW 100 is manufactured at our plant under strict quality control.

SPECIFICATIONS

<p>Input Voltage 95V to 264Vac 47 - 420Hz DC-input also available. Please consult factory.</p> <p>Input Protection Inrush current limiting Varistor Internal safety fuse Lower voltage than the specified minimum input will not damage the unit</p> <p>Isolation 2250VDC input to chassis 4300VDC input to output 8mm spacing 500VDC output to chassis</p> <p>Standards Designed to meet EN 60950 and corresponding UL and CSA standards. Several versions have formal agency approvals</p> <p>EMI EN55022 Class B</p> <p>Switching Frequency 47 kHz +/-2kHz</p> <p>Hold Up Time Minimum 5ms at full load for 5% drop of output voltage at > 120Vac input</p>	<p>Output Voltages 5Vdc/15A, 12Vdc/8A, 24Vdc/4A; 36Vdc/3A, 48Vdc/2A, 72Vdc/1.5A or 130Vdc/0.75A are standard. Consult factory for other voltages.</p> <p>Redundancy Diode None</p> <p>Line/Load Regulation +/- 1% combined from zero load to full load</p> <p>Dynamic Response Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time</p> <p>Output Ripple/Noise Less than 1% of output voltage peak to peak or 0.2% RMS of the output voltage (20MHz BW)</p> <p>Output Overload Protection Rectangular current limiting with hiccup mode short-circuit protection on both outputs Thermal shutdown in case of insufficient cooling (self resetting)</p> <p>Output Overvoltage Protection Double regulator loop</p>	<p>Efficiency Output voltage dependent. Typically better than 80% at full load</p> <p>Operating Temperature Range 0 to 50°C for full specification installed on heat-sinking surface with good air flow Extended temperature ranges available</p> <p>Temperature Drift 0.03% per °C over operating temperature</p> <p>Cooling Conduction to customer heatsink or chassis and natural convection</p> <p>Environmental Protection Basic ruggedizing Full ruggedizing and conformal coating available as an option</p> <p>Shock/Vibration IEC 61373 Cat 1 A&B</p> <p>Humidity 5 – 95% non-condensing</p> <p>MTBF 160,000 hours @ 45 °C Demonstrated MTBF is significantly higher</p>	<p>Indicators None on standard version</p> <p>Control Input None</p> <p>Alarm Output None</p> <p>Packaging/Dimensions <u>Open PCB version:</u> PCB size 3" x 5" Component height: 1.5" Connector: header pins with 0.156" spacing or barrier-type terminal block Weight: 0.2 kg (0.5 lb)</p> <p><u>Enclosed case version (F0):</u> 94 x 48 x 160 mm (W x H x L) (3.7" x 1.9" x 6.3") including terminal block and flanges. Mounting holes are clear Connector: 6 pole barrier-type terminal block with 3/8" spacing. Weight: 0.55 kg (1.2 lb)</p> <p>RoHS Compliance Fully compliant</p> <p>Warranty Two years subject to application within good engineering practice</p>
--	---	---	--

Enhancements to these general specifications and customizing can be accommodated upon request. Specifications subject to change.

Designer and manufacturer of quality converters, inverters, DC-output UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BAPT-approved Facility.



ABSOPULSE ELECTRONICS LTD
110 Walgreen Road
Ottawa, Ontario. K0A 1L0. CANADA
Tel: (613) 836-3511 Fax: (613) 836-7488
E-mail: absopulse@absopulse.com
www.absopulse.com