

300W, Dual Output, Rugged, AC/DC Industrial Power Supply with Universal Input MIW 302-FT Series

- Rugged industrial quality
- Two regulated and adjustable output
- Conduction/convection cooled
- Full electronic protection
- Wide selection of input/output combinations
- Field proven design
- N+1 redundancy available



The MIW 302 Series rugged, dual output AC/DC industrial power supply uses field proven technology to generate 300W output power. This mature design is built on the KIW 302 PCB and has a track record in numerous of applications. The unit has two completely independent converter stages to provide 150W on each output. The outputs are floating and can be connected in series to generate high output voltage (100 – 250Vdc) or in parallel to increase the output current. Adjustments for both outputs are accessible. An optional built-in redundancy diode allows for the outputs to be connected in parallel for 1+1 redundancy, or handle high peak load currents. Other options include a built-in alarm and a wide range of output configurations. The unit has full electronic protection. Low component count, large design headroom, and the use of components with established reliability result in a high MTBF. Additional ruggedizing and conformal coating are available for operation in extreme environments. The MIW 302 is manufactured at our plant under strict quality control. Customized versions are also available.

SPECIFICATIONS

<p>Input Voltage 95V to 264Vac 47 - 420Hz DC-input also available. Please consult factory.</p> <p>Input Protection Inrush current limiting Varistor Internal safety fuse Lower voltage than the specified minimum input will not damage the unit</p> <p>Isolation 2250VDC input to chassis 4300VDC input to output 8mm spacing 500VDC output to chassis</p> <p>Standards Designed to meet EN 60950 and corresponding UL and CSA standards</p> <p>EMI EN55022 Class B</p> <p>Switching Frequency 47 kHz +/-2kHz</p> <p>Hold Up Time Minimum 5ms at full load for 5% drop of output voltage at > 120Vac input</p>	<p>Output Voltage/Current Up to 125Vdc per output Up to 15 Amps per output Outputs are floating and can be connected in series or parallel.</p> <p>Redundancy Diode Optional built-in redundancy diode</p> <p>Line/Load Regulation +/- 1% combined from zero load to full load</p> <p>Dynamic Response Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time</p> <p>Output Ripple / Noise Less than 1% of output voltage peak to peak or 0.2% RMS of the output voltage (20MHz BW)</p> <p>Output Overload Protection Rectangular current limiting with short-circuit protection on both outputs (hiccup mode) Thermal shutdown with automatic recovery in case of insufficient cooling</p> <p>Output Overvoltage Protection Second regulator loop on both outputs</p>	<p>Efficiency Min. 80% at full load</p> <p>Operating Temperature Range 0 to 50°C for full specification installed on heat-sinking surface with good air flow Extended temperature ranges available</p> <p>Temperature Drift 0.03% per °C over operating temperature range</p> <p>Cooling Conduction via base plate to customer heatsink or chassis and natural convection</p> <p>Environmental Protection Basic ruggedizing Full ruggedizing and conformal coating available as an option</p> <p>Shock/Vibration IEC 61373 Cat 1 A&B</p> <p>Humidity 5 – 95% non-condensing</p> <p>MTBF 140,000 hours @ 45 °C Demonstrated MTBF is significantly higher.</p>	<p>Indicators None on standard version</p> <p>Control Input None</p> <p>Alarm Output None on standard version Available as option</p> <p>Package/Dimensions (W x H x D) F3: 132 x 62 x 300 mm (5.2" x 2.4" x 11.8") including mounting flanges and terminals. Mounting holes are clear</p> <p>Weight 2 kg (4.4 lb)</p> <p>Connections 12 pole barrier type terminal block with 3/8" spacing</p> <p>RoHS Compliance Fully compliant</p> <p>Warranty Two years subject to application within good engineering practice</p>
---	--	--	--

Enhancements to these general specifications and customizing can be accommodated upon request. Specifications subject to change.

Designer and manufacturer of quality converters, inverters, UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility.



ABOPULSE ELECTRONICS LTD
110 Walgreen Road
Ottawa, Ontario. K0A 1L0. CANADA
Tel: (613) 836-3511 Fax: (613) 836-7488
E-mail: absopulse@absopulse.com
www.absopulse.com