

## 800W POWER SUPPLY IN 5" X 5" X 12" PACKAGE BAP 800 SERIES

- Competitive price
- Stock or short delivery
- Compact size
- Full electronic protection
- Made in North America
- Telecom quality
- Field-proven design topology



The BAP 800 Series is a compact DC/DC converter which uses established design techniques to deliver up to 1000W output power depending on the input/output configuration. A wide selection of input and output voltages are available off-the-shelf or with short lead times. Suitable for a wide range of applications, the BAP 800 features full electronic protection, high efficiency and low output noise. The built-in fan provides sufficient airflow for operation without de-rating up to 50°C ambient temperature. Options include extended operating temperature (-40 to +65°C) and N+1 redundancy.

### SPECIFICATIONS

**Input Voltage**

21-30VDC and 42-60VDC ranges standard. Other inputs upon request

**Input Protection**

Thermal fuse  
Inrush current limiting

**Input Isolation/Safety**

1000VDC input to chassis  
1000VDC input to output  
500VDC output to chassis

Full compliance to IEC950, CSA 22-2-950 and UL 1950

Please consult factory for approval status for the requested input/output configuration

**Output Voltages**

12V/66A; 24V/33A; 48V/16A; or 120V/6.6A are standard  
Consult factory for other voltages and output currents

**Efficiency**

Typical 90% at full load

**Line/Load Regulation**

± 1% combined  
Tighter regulated versions with sensing available

**Output Overvoltage Protection**

Double regulator loop

**Overload Protection**

Rectangular current limiting with short circuit protection  
Thermal shutdown with automatic reset in case of insufficient airflow

**EMI**

EN 55022 Class A  
Class B versions available

**Output Ripple/Noise**

Better than 1% of output voltage peak to peak or 0.2% RMS of the output voltage (20MHZ BW)  
Audio band noise: max. 32dBmC

**Operating Temperature**

0°C to +50°C

**Temperature Drift**

0.03% per °C over operating temperature range

**Dimensions**

5" x 5" x 11.5" enclosed case  
Can be mounted on a 3U x19" or 23" panel for rack mount applications

**Connections**

Copper studs with nuts or terminal block

**Output Fail Alarm**

via optocoupler - C-E  
(normal operation: low)

**Warranty:** Twelve months subject to application within good engineering practice  
Enhancements to these general specifications can be accommodated upon request  
Designed to meet common approval requirements. Specifications subject to change.

**Designer and manufacturer of quality converters, inverters, UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard.**

**Absopulse is a BAPT-approved Facility**

**ABSOPULSE**  
ELECTRONICS LTD.

**ABSOPULSE ELECTRONICS LTD**  
110 Walgreen Road  
Carp, Ontario K0A 1L0 CANADA

Tel: (613) 836-3511 Fax: (613) 836-7488 E-mail: [absopulse@absopulse.com](mailto:absopulse@absopulse.com)  
Visit us at [www.absopulse.com](http://www.absopulse.com)