

Redundant AC/DC Converter System with 500W Plug-in Modules for Professional Applications HBC 419 Series

- Rugged industrial quality
- 4U x 19" x 15" shelf
- 500W per module or 2500W per 19" shelf
- Front panel adjustment & LED status
- Hot insertable
- N+1 redundancy
- Fully protected
- Field-proven design in wide range of applications



This system is comprised of up to five rugged, industrial quality AC/DC plug in power supply modules and uses field-proven topology to generate the required output power. It is a mature design with large design headrooms and rated for operation over a wide temperature range without derating. The strict use of components with many years of established reliability results in a high demonstrated MTBF confirmed by a track record in hundreds of applications. Each module has a built-in redundancy diode which allows for an unlimited number of units to be paralleled for higher output power and N+1 redundant operation. The built-in redundancy also allows battery connection to the output for back-up purposes. The modules are hot insertable. Modules with different outputs can be combined in one shelf to create a multi-output system. The plug-in modules are cooled by natural air convection. Heat generating components are installed on an aluminum heatsink block, which is connected to the large heatsink on the side of each module. The unit has full electronic input/output protection, and meets EMI emission standards with wide margins. The design is optimized for low component count and high efficiency. The whole system is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage

115/230VAC +/- 15%
47 - 63Hz

Please consult factory for other voltages and ranges

Input Protection

Inrush current limiting
Varistor
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Input Isolation

2250VDC input to chassis
4300VDC input to output,
8mm spacing
500VDC output to chassis
Isolation voltages correspond to input/output combination

Standards

Designed to meet EN 60950 and related standards.

EMI

EN 55022 Class A as a minimum

Switching Frequency

55KHz +/- 3KHz

Output Voltages/Currents

24V/20A and 48V/10A
500W per module with convection cooling
Consult factory for other voltages

Redundancy Diode

Installed on each plug-in module

Line/Load Regulation

Typically $\pm 1\%$ combined from no load to full load (depending on output voltage)

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple/Noise

Better than 1% of output voltage peak to peak or 0.2% RMS of the output voltage (20HZ BW)

Output Overload Protection

Rectangular current limiting with short circuit protection (constant current)
Thermal shutdown with automatic recovery in case of reduced airflow

Output Overvoltage Protection

Second regulator loop

Efficiency

85% typical depending on the input/output configuration

Operating Temperature

0 to +50°C (standard model with convection cooling)
Extended temperature range available

Temperature Drift

0.03% per °C over operating temperature range

Cooling

Natural air convection

Environmental Protection

Basic ruggedizing.
Conformal coating and full ruggedizing as option

MTBF

180,000 hours at 45°C per plug-in module.
Demonstrated MTBF is significantly higher

Indicators

Output ON LED
Test Points on front-panel

Controls

Adjustment potentiometer on front-panel

Alarm Output

Form C module fail alarm on the shelf.
Optocoupler alarm on the module

Mechanical

4U x 16HP x 304mm (module)
4U x 19" x 15" (shelf)
including connections

Connections:

H15 DIN connector on modules.
Terminal block for shelf
Other terminations available,
please consult factory

RoHS Compliance

Fully compliant

Warranty

Two years subject to application within good engineering practice

Enhancements to these general specifications can be accommodated upon request. Specifications subject to change.

Designer and manufacturer of quality converters, inverters, UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa
Ontario, K0A 1L0, CANADA
Tel: (613) 836-3511 Fax: (613) 836-7488
E-mail: absopulse@absopulse.com
www.absopulse.com