

100W, Rugged DC/DC Converter for Railway and other Demanding Environments

DCW 100R Series



- Field-proven rugged design
- For train and mobile applications
- Conduction/convection cooled – no fan
- Full electronic protection
- Wide selection of input/output combinations

The DCW 100R Series rugged, railway quality DC/DC converter uses field proven topology to generate the required output power. It is a mature design with a track record in numerous applications. Cooling is by conduction via base plate to a heat-sinking surface and by natural convection. Ruggedizing and conformal coating provide added immunity to shock, vibration and humidity. Full electronic protection, large design headroom, and the use of components with established reliability result in a high MTBF. The series meets the requirements of EN 50155 for electronic equipment used on railway rolling stock. The units are manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage (nominal/range)

48Vdc (29 - 67V)
72Vdc (43 - 101V)
96Vdc (58 - 135V)
110Vdc (66 - 154V)
Other inputs upon request

Input Protection

Inrush current limiting
Varistor
Reverse polarity protection
Internal safety fuse
Lower voltage than the specified
Minimum input will not damage the unit

Isolation

1500Vdc input to chassis
3000Vdc input to output
1500Vdc output to chassis

Standards

Designed to meet EN60950 and EN50155

Immunity

Meets criteria of EN50155 and EN50121-3-2 including:
EN 61000-4-2 (ESD)
EN 61000-4-3 (RF Immunity)
EN 61000-4-4 (Fast Transients)
EN 50155 (Surge)
EN 61000-4-6 (Conducted Imm.)
EN 50155 (Voltage Variations)

EMI

EN55022 Class B and EN50121-3-2 conducted and radiated

Switching Frequency

47KHz +/- 2KHz

Output Voltage/Current

12V/8A, 24V/4A, 48V/2A or 110A/0.9A are standard. Derating may be required depending on input voltage Consult factory for other voltages and higher power rating

Redundancy diode

None

Line/Load Regulation

+/-1% combined from no load to full load

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple/Noise

Better than 1% of output voltage peak to peak or 0.2% RMS of the output voltage (20MHZ BW)

Overload Protection

Current limiting with hiccup type short circuit protection

Output Overvoltage Protection

Double regulator loop and transzorb

Efficiency

80 to 90% at full load depending on input/output configuration

Operating Temperature

-25 to +70°C cold-plate temperature for full specification

Temperature Drift

0.03% per °C over operating temperature range

Cooling

Conduction via base plate to customer heat-sink or chassis and natural convection

Environmental Protection

Ruggedizing
Conformal coating

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 – 95% non-condensing

MTBF

Min. 150,000 hours @45°C
Demonstrated MTBF is significantly higher

Indicators

None

Control Input

None

Alarm Output

None
Available as option

Package/Dimensions (W x H x L)

F0: 94 x 48 x 160 mm (3.7" x 1.9" x 6.3") including terminal block and flanges
Mounting holes are clear.

Weight

0.55kg (1.2 lbs)

Connections

6-pole barrier-type terminal block, 3/8" spacing

RoHS

Fully compliant

Warranty

Two years subject to application within good engineering practice

Standard Terminal Block Pin-Out

OUTPUT			INPUT		
-	+	NOT USED	GND	+	-
1	2	3	4	5	6

Note: A few existing designs of this extensive series have a slightly different Pin-out

Enhancements to these general specifications and customizing can be accommodated upon request. Specifications are subject to change.

Designer and manufacturer of quality ac-dc power supplies and battery chargers, converters, inverters, dc-output UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility.



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road
Ottawa, Ontario. K0A 1L0. CANADA
Tel: (613) 836-3511 Fax: (613) 836-7488
E-mail: absopulse@absopulse.com
<http://www.absopulse.com>