

100W, Encapsulated AC/DC Power Supply for Heavy Duty Applications PWI 100 Series

- Rugged, field proven design
- Conduction cooling
- Fully encapsulated
- Full electronic protection
- Universal input ranges



This fully encapsulated, rugged, industrial quality AC/DC power supply uses field-proven technology to generate 100W output power. It is a mature product with a track-record in numerous applications. The unit is entirely potted with a thermally conductive MIL-grade silicon rubber compound to provide immunity to shock, vibration and humidity. It is conduction cooled via a base-plate to a heat-sinking surface. Full electronic protection, low component count, large design headroom, and the use of components with established reliability ensure high MTBF. The unit is suitable for transportation, mining, oilrigs, military and other harsh environments. The converter is manufactured at our plant under strict quality control. Versions that are designed to meet EN 50155 railway specifications are also available.

SPECIFICATIONS

Input Voltage

Universal input
95Vac - 264Vac, 47-63Hz
DC-input also available
Consult factory for other voltages

Input Protection

Inrush current limiting
Varistor
Internal safety fuse
Line to GND varistor upon request
Lower voltage than the specified minimum input will not damage the unit

Isolation

2250VDC input to chassis
4300VDC input to output;
8mm spacing
500VDC output to chassis

Standards

Designed to meet EN60950-1 and corresponding UL and CSA standards

EMI

EN55022 Class A with margins

Switching Frequency

47kHz \pm 2kHz

Hold-Up Time

Minimum 5ms at full load for 5% drop of output voltage at 120V AC input.

Output Voltage/Current

12Vdc/8A, 24Vdc/4A or 48Vdc/2A
Output is floating, either terminal can be grounded
Consult factory for other voltages

Redundancy Diode

None

Line/Load Regulation

\pm 1% combined from zero load to full load

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple/Noise

Better than 1% of output voltage peak to peak or 0.2% RMS of the output voltage. (20MHz BW)

Output Overload Protection

Rectangular current limiting with short-circuit protection (hiccup type)

Output Over-voltage Protection

Double regulator loop completely stable and independent of main regulator loop

Efficiency

Output is voltage dependent.
Typically 80% at full load

Operating Temperature Range

-40°C to +70°C cold-plate temperature for full specification

Temperature Drift

0.03% per °C over operating temperature range.

Cooling

Conduction via base plate to customer heatsink or chassis

Environmental Protection

Full encapsulation with thermally conductive silicon potting compound with UL94V-0 flammability rating.
Meets environmental criteria as requested in MIL-810 C, D

Shock/Vibration

IEC 61373 Cat 1 A&B

MTBF

180,000 hours @ 45 °C
Demonstrated MTBF significantly higher

Indicators

None

Control Input

None

Alarm output

None

Package/Dimensions (W x H x L)

P99L: 81 x 61 x 156mm (3.2" x 2.4" x 6.2") including terminal blocks and flanges.
Mounting holes are clear.

Weight

0.95 kg (2 lb)

Connections

6 pole barrier type terminal block, 3/8" spacing. Snap-on cover available.

RoHS Compliance

Fully compliant

Warranty

Two years subject to application within good engineering practice

Terminal Block Pin-out

DC OUTPUT			AC INPUT		
-	+	NOT USED	$\frac{1}{2}$	PH	N
1	2	3	4	5	6

Enhancements to these general specifications can be accommodated upon request. Specifications are subject to change.

Designer and manufacturer of quality converters, inverters, UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario | K0A 1L0 | CANADA

Tel: +1-613-836-3511 | Fax: +1-613-836-7488

E-mail: absopulse@absopulse.com | <http://www.absopulse.com>

For more information, please see:

[http://www.absopulse.com/Absopulse AC DC powersupplies batterychargers.php](http://www.absopulse.com/Absopulse_AC_DC_powersupplies_batterychargers.php)

August 29, 2014/TS/CL

Made in Canada