

## 200W, Rugged, Industrial Quality DC/DC Converter BAP 200-FT Series



- Rugged industrial quality
- Field-proven design
- Regulated and adjustable output
- Conduction/convection cooling (no fans)
- Full electronic protection
- N+1 redundancy by built in diode as option

This rugged, industrial quality DC/DC converter uses field-proven topology to generate up to 200W output power. It is a mature design with a track record in numerous applications. Cooling is via baseplate to a heat-sinking surface and by natural convection. An optional built-in redundancy diode allows for parallel and N+1 operation. Additional ruggedizing and conformal coating are available on request for applications that require immunity to high levels of shock, vibration and humidity. Full electronic protection, low component count, large design headrooms, and the use of components with established reliability result in a high MTBF. The series is manufactured at our plant under strict quality control.

### SPECIFICATIONS

#### Input Voltage

24Vdc (21-29V)  
48Vdc (42-56V)  
125Vd (105-145V)  
For 12Vdc and other input voltages, consult factory.

#### Input Protection

Inrush current limiting  
Varistor  
Reverse polarity protection  
Internal safety fuse  
Lower voltage than the specified minimum input will not damage the unit

#### Isolation

According to input voltage minimum of:  
1000VDC input to chassis,  
1500VDC input to output,  
500VDC output to chassis

#### Standards

Designed to meet EN60950 and corresponding standards

#### EMI

EN 55022 Class A with margins

#### Switching Frequency

55KHz +/- 3kHz

#### Output Voltages

12V/16A, 24V/8A, 48V/4A or 125V/1A  
Total output power 200W continuous  
Output is floating; either terminal can be grounded  
Consult factory for other voltages

#### Redundancy Diode

Installed on request

#### Line/Load Regulation

+/- 1% combined from zero load to full load including redundancy diode

#### Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

#### Output Ripple / Noise

Better than 1% of output voltage peak to peak or 0.2% Vrms (20MHz BW)

#### Output Overload Protection

Rectangular current limiting with short-circuit protection (No hiccup)  
Thermal shutdown in case of insufficient cooling (self- resetting)

#### Output Overvoltage Protection

Double regulator loop completely stable and independent of main loop

#### Efficiency

80% - 87% at full load, depending on output voltage

#### Operating Temperature Range

0 to + 50°C for full specification (For extended temperature range see BAP 236 Series)

#### Temperature Drift

0.03% per °C over operating temperature range

#### Cooling

Conduction via base plate to customer heat sink or chassis and natural convection

#### Environmental Protection

Basic ruggedizing  
Heavy ruggedizing and conformal coating as option

#### Shock/Vibration

IEC 61373 Cat 1 A&B

#### Humidity

5 - 95% non-condensing

#### MTBF

150,000 hours at 45 °C  
Demonstrated MTBF is significantly higher.

#### Indicators

Green "Output ON" LED visible through the cooling slots

#### Control Input

None

#### Alarm Output

Output fail alarm Form C contacts installed on request

#### Package/Dimensions (W x H x L)

F2: 114 x 58 x 256 mm (4.5" x 2.3" x 10.1") including terminal block and flanges  
Mounting holes are clear

#### Weight

1.2 kg (2.6 lb)

#### Connections

9-pole barrier type terminal block with 3/8" spacing

#### RoHS Compliance

Fully compliant

#### Warranty

Two years subject to application within good engineering practice

#### Terminal Block Pin-out

ALARM (OPTION)			DC OUTPUT			DC INPUT		
FAIL OPEN	COM	FAIL CLOSED	-	+	NOT USED	GND	-	+
1	2	3	4	5	6	7	8	9

Enhancements to these general specifications can be accommodated upon request. Specifications are subject to change.

*Designer and manufacturer of quality converters, inverters, UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility*



#### ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario | K0A 1L0 | CANADA

Tel: +1-613-836-3511 | Fax: +1-613-836-7488

E-mail: [absopulse@absopulse.com](mailto:absopulse@absopulse.com) | <http://www.absopulse.com>