

2.5kW Rugged, Industrial Quality, Rack-mount AC/DC Power System with Convection Cooled Plug-in Modules PFC 419-2.5K-4U19 Series

- Electronic power factor correction (PFC)
- Rugged industrial quality
- Up to 2500W per 19" shelf
- Up to 500W per plug-in module
- Full electronic protection
- Convection cooled
- Field-proven design
- Hot swappable, N+1 redundant



PFC 419-EH plug-in module (500W)
4U x 16HP x 304mm



Fully loaded PFC 419F-2.5K-4U19 system

This is a modular, industrial quality AC/DC power supply system with power factor corrected input. It can be built with up to five, 500W plug-in modules assembled in a 4U x 19" card-frame that delivers a maximum of 2500W or 2000W with N+1 redundancy. Each hot-insertable module has a built-in redundancy diode which allows for parallel connection and N+1 redundant operation. This feature also makes the system suitable for battery charging. Each plug-in module is cooled by natural air convection. This mature design has large design headroom and is rated for operation over the specified temperature range without de-rating. Full electronic protection and the use of components with established reliability results in a high demonstrated MTBF confirmed by a track record in numerous applications. The system is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage

95-264Vac (Universal) 47... 63Hz
Input Current: 7Arms max. per plug in module
Power Factor is better than 0.97 at full load for the entire input range.
Meets EN61000-3-2

Input Protection

On each plug-in module:
Inrush current limiting
Varistor
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

2250VDC input to chassis
4300VDC input to output
8mm spacing
500VDC output to chassis

Standards

Designed to meet EN60950-1 and related standards.

EMI

EN 55022 Class A with margins

Switching Frequency

See plug-in module data sheet

Hold Up Time

Min. 10ms at any input for 5% drop in the output voltage

Output Voltage/Current

24V/20A, 48V/10A, 110V/4.5A or 125V/4A per module with convection cooling
Max output 500W per module
Max output 2500W per shelf
Consult factory for other outputs

Redundancy Diode

Installed on each plug-in module
Hot insertion allowed

Line/Load Regulation

±1.5% combined from zero load to full load including redundancy diode

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple/Noise

Better than 0.2% RMS or 1% of output voltage peak-to-peak (20MHz BW)

Overload Protection

Rectangular current limiting with short-circuit protection (constant current)
Thermal shutdown on each module in case of insufficient cooling (self-resetting)

Output Overvoltage Protection

Each plug in module has over voltage protection

Efficiency

Output voltage dependent
Typically 80% at full load

Operating Temperature Range

0°C to 50°C for full specification
Extended temperature range available on request

Temperature Drift

0.03% per °C over operating temperature range

Cooling

Natural air convection

Environmental Protection

Basic ruggedizing
Heavy ruggedizing and conformal coating as option

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 – 95%, non-condensing

MTBF

135,000 hours @ 45 °C
Per plug-in module
Demonstrated MTBF is significantly higher.

Indicators

On front panel of each module:
Green "Output ON" LED connected before redundancy diode

Controls

None
Options available

Alarm Output

Form C Module fail alarm on shelf
Optocoupler alarm on the module (C-E opens on alarm)

Package/Dimensions (W x H x D)

4U x 19" x 15" (shelf) including connections
4U x 16HP x 304mm (plug-in modules)

Weight

Empty frame: 5.2kg
Each plug-in module: 2.2kg
Fully loaded: 16.2 kg

Connections

H15 Connector on plug-in module
Terminal blocks on the shelf

RoHS Compliance

Fully compliant

Warranty

Two years subject to application within good engineering practice

Enhancements to these general specifications and customizing can be accommodated upon request. Specifications are subject to change.

Designer and manufacturer of quality converters, inverters, UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario. K0A 1L0. CANADA

Tel: +1-613-836-3511 | Fax: +1-613-836-7488

E-mail: absopulse@absopulse.com | <http://www.absopulse.com>