

4.5kW Rugged, Industrial Quality Rack-mount AC/DC Power System with 1.5kW Modules PFC 4K5-CR3U/19-3 Series

- Electronic power factor correction (PFC)
- Rugged industrial quality
- Up to 4500W per 19" shelf
- Full electronic protection
- Fan cooling
- Field-proven design
- Hot swappable, N+1 redundant



PFC 1K5 module: 5 x 5 x 12"
(depth excludes connector)



3U x 19" stainless steel cradle with 3 x PFC 1K5 modules

This modular, industrial quality AC/DC power supply system with power factor corrected input is built with three 1500W, PFC 1K5 power supply modules assembled on a 3U x 19" stainless steel cradle ([CR 3U/19-3](#)). The PFC 1K5 units are equipped with connectors which allow hot insertion. A built-in redundancy diode in each module allows for parallel connection and N+1 redundant operation. The system delivers a maximum of 4500W or 3000W with N+1 redundancy. The PFC 1K5 modules are based on field-proven topology. They have large design headroom and are rated for operation over the specified temperature range without de-rating. Each module is cooled by a high quality built-in fan. Full electronic protection and the use of components with established reliability results in a high demonstrated MTBF confirmed by a track record in numerous applications. The system is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage per PFC1K5 Module

95-264Vac (Universal) 47... 63Hz
Input Current: 18Arms max.
Power Factor is better than 0.97 at full load for the entire input range.
Meets EN61000-3-2 and EN61000-3-12

Input Protection

On each module:
Inrush current limiting
Varistor
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

2250VDC input to chassis
4300VDC input to output
8mm spacing
500VDC output to chassis

Standards

Designed to meet EN60950-1 and related standards.

EMI

EN 55022 Class A with margins

Hold-Up Time

Minimum 10ms at full load for 5% drop of output voltage at nominal input

Switching Frequency per Module

100kHz input section
55kHz output section

Output Voltage/Current per Module

24V/60A, 48V/30A, 54V/27A
110V/13A or 125Vdc/12A per module with fan cooling
Output is floating, either terminal can be grounded
Max output 1500W per module
Max output 4500W per shelf
Consult factory for other outputs

Redundancy Diode

Installed on each module
Hot insertion allowed

Line/Load Regulation

±2% combined from zero load to full load including redundancy diode

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple/Noise

Better than 1% of output voltage peak to peak or 0.2% RMS of the output voltage (20MHz BW)

Overload Protection

Rectangular current limiting with short-circuit protection (no hiccup)
Thermal shutdown on each module in case of insufficient cooling (self-resetting)

Output Overvoltage Protection

Second regulator loop, completely stable and independent of main regulator loop

Efficiency

Output voltage dependent
Typically 80% at full load

Operating Temperature

0°C to 50°C for full specification
Extended temperature range available on request

Temperature Drift

0.03% per °C over operating temperature range

Cooling

Each module has one high quality built in fan

Environmental Protection

Basic ruggedizing
Heavy ruggedizing and conformal coating as option

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5-95% non-condensing

MTBF

120,000 hours @45°C per module.
Demonstrated MTBF is significantly higher.
Fans are not included.

Indicators

Diagnostic Output ON LED visible through the rear cooling slots

Controls

None
Options available

Alarm Output

Module fail alarm Form C on each module

Package/Dimensions (H x W x D)

Stainless steel rack-mount cradle, [CR 3U/19-3](#): 3U x 19" x 12.4"
PFC 1K5 modules in M5512.
127 x 127 x 460mm (5" x 5" x 18.1")
Depth (460mm) includes Anderson SB175A connectors

Weight

3U system with 3x PFC1K5 modules: 20kg (44 lbs) approx.

Connections

Input: IEC receptacle
Output: Anderson Connector SB175A
Alarm: Phoenix MSTBA 2.5/3-G on each module

RoHS Compliance

Fully compliant

Warranty

Two years subject to application within good engineer

Enhancements to these general specifications and customizing can be accommodated upon request. Specifications are subject to change.

Designer and manufacturer of quality converters, inverters, UPS systems, complete rack-mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario. K0A 1L0. CANADA
Tel: +1-613-836-3511 | Fax: +1-613-836-7488

E-mail: absopulse@absopulse.com | <http://www.absopulse.com>