

## 300VA Sine Wave Inverter for Railway Applications RSI 300-FT Series



- Field-proven rugged design
- Conduction/convection cooled - no fan
- Low profile, compact size
- Sinusoidal wave shape
- Full electronic protection

This rugged DC/AC inverter uses field proven, microprocessor controlled high frequency PWM technology to generate the required output power with pure sine wave output voltage. It is a mature design with a track record in numerous applications. The DC/DC input stage boosts the input voltage to a higher DC voltage, which feeds the DC/AC inverter to generate the required AC output. The high frequency conversion enables a compact construction, low weight and high efficiency. The unit has full electronic protection. The input and output are filtered for low noise. Cooling is via baseplate to a cold plate surface and by additional natural convection. The use of components with established reliability results in high MTBF. The unit meets the requirements of EN 50155 for electronic equipment used on railway rolling stock. It is manufactured at our plant under strict quality control. Customized versions are available.

### SPECIFICATIONS

#### Input Voltage

24Vdc (17 – 34V)  
36Vdc (25 – 51V)  
48Vdc (33 – 67V)  
72Vdc (50 – 101V)  
96Vdc (67 – 135V)  
110Vdc (77 – 154V)  
Consult factory for other  
input voltages and ranges

#### Input Protection

Inrush current limiting  
Varistor  
Reverse polarity protection  
Internal safety fuse  
Lower voltage than the specified  
minimum input will not damage  
the unit

#### Isolation

1500Vdc input to chassis  
3000Vdc input to output

#### Standards

Designed to meet  
C22.2 No. 107.1 - 01, UL 458,  
EN60950 and EN50155

#### Immunity

Meets criteria of EN50155 and  
EN50121-3-2 including  
EN 61000-4-2 (ESD)  
EN61000-4-3 (RF Immunity)  
EN61000-4-4 (Fast transients)  
EN50155 (Surge)  
EN61000-4-6 (Conducted Imm.)  
EN50155 (Voltage Variations)

#### EMI

EN55022 Class A or B according  
to requirements and  
EN50121-3-2 conducted and  
radiated

#### Output Voltage

115Vac @60Hz or 400Hz/2.6Arms  
continuous; or  
230Vac @ 50Hz/1.3Arms  
continuous  
Isolated floating output  
Consult factory for other output  
requirements

#### Output Wave Form

Sinusoidal

#### Total Harmonic Distortion

Less than 5% at full load

#### Line Regulation

Maximum 0.5%

#### Load Regulation

Maximum  $\pm 2\%$  from no load  
to full load.

#### Load Crest Factor

Maximum 3.0 at 90% load

#### Output Noise

High frequency ripple is less  
than 500mVrms (20MHz BW)

#### Output Overload Protection

Current limiting with short circuit  
protection  
Thermal shutdown with automatic  
recovery in case of insufficient  
cooling

#### Output Overvoltage Protection

140Vac (for 115Vac output) or  
280Vac (for 230Vac output) by  
internal supply voltage limiting

#### Efficiency

Typically 80% at full load  
Dependent on input/output  
combination

#### Operating Temperature

-25 to +50°C cold-plate  
temperature for full specification

#### Temperature Drift

0.05% per °C over operating  
temperature range

#### Cooling

Conduction to customer heat-sink  
or chassis and natural convection

#### Environmental Protection

Ruggedizing  
Conformal coating

#### Shock/Vibration

IEC 61373 Cat 1 A&B

#### Humidity

5 - 95% non-condensing

#### MTBF

150,000 hours at 45 °C  
Demonstrated MTBF is  
significantly higher

#### Indicators

None

#### Control Input

None

#### Alarm Output

Optional output Fail Alarm (Form C)

#### Dimensions

FX: 153 x 67 x 357 mm  
(6" x 2.7" x 14.1") including  
terminal block and flanges  
Mounting holes are clear

#### Weight

Approx. 2.2 kg (5 lb.)

#### Connections

Barrier-type terminal block  
with 3/8" spacing

#### RoHS Compliance

Fully compliant

#### Warranty

Two years subject to application  
within good engineering practice

### Terminal Block Pin-Out

AC OUTPUT			ALARM			DC INPUT					
L1	L2	NOT USED	FAIL OPEN	COM	FAIL CLOSED	NOT USED	GND	-	-	+	+
1	2	3	4	5	6	7	8	9	10	11	12

**Please note that ABSOPULSE inverters are designed and built to customer specifications. The specifications on this data sheet are generic and will vary depending on input/output configuration and other customer requirements. Generic specifications are subject to change.**

*Designer and manufacturer of quality converters, inverters, UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility*



#### ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario. K0A 1L0. CANADA

Tel: +1-613-836-3511 | Fax: +1-613-836-7488

E-mail: [absopulse@absopulse.com](mailto:absopulse@absopulse.com) | <http://www.absopulse.com>

For more information, please see:

[http://www.absopulse.com/Absopulse\\_railway\\_mobile\\_extreme\\_environment\\_solutions.php](http://www.absopulse.com/Absopulse_railway_mobile_extreme_environment_solutions.php)

November 7, 2012/TS/OP/CL

Made in Canada