

2000VA Rugged, Industrial Quality Frequency Converter with Sine Wave Output FC 2K Series

- Rugged construction
- Sinusoidal output voltage
- Filtered input
- Cooling by internal fans
- Full electronic protection
- Field-proven design topology

3U3+3U4:
3U x 9.6" x 16"
plus
3U x 7.4" x 16"
rack-mount or
chassis mount.



3U7:
3U(5.2") x 19" x 16"
rack-mount or
chassis mount.



Mechanical size depends on input/output configuration.
Chassis-mount and 19" rack-mount versions available on most designs

This rugged, AC/AC frequency converter system uses field proven, microprocessor controlled high frequency PWM technology to generate the required output power with pure sine wave output voltage. It is a mature design with a track record in numerous applications. The frequency converter is built with internal power modules. The AC/DC input stage boosts the input voltage to a higher DC voltage, which feeds the DC/AC inverter to generate the required AC output. Built-in fans provide sufficient airflow for operation without de-rating to the specified temperature. The high frequency conversion enables a compact construction, low weight and high efficiency. The unit has full electronic protection. The input and output are filtered for low noise. The use of components with established reliability results in high MTBF. The system is manufactured at our plant under strict quality control. Customized versions are also available.

SPECIFICATIONS

Input Voltage

115 or 230Vac, +/-15%
47 ... 410Hz are standard
Factory set for required input
95 – 264Vac universal input with
PFC is also available

Input Protection

Inrush current limiting
Varistors
Internal safety fuse
Lower voltage than the specified
minimum input will not damage
the unit

Isolation

2250Vdc input to chassis/output
Output neutral is connected to
the chassis internally
Floating output as option

Standards

Designed to meet
C22.2 No. 107.1 - 01,
UL 458 and EN60950

EMI

EN 55022 Class A
as a minimum

Output Voltage

115Vac @ 60Hz or
400Hz/17.4A rms continuous;
or 230Vac @ 50Hz/8.7A rms
continuous.
Output neutral is connected to the
chassis internally.
Isolated floating output optional
Consult factory for other outputs

Output Wave Form

Sinusoidal

Total Harmonic Distortion

Less than 5% at full load

Line/Load Regulation

Maximum ± 6% from no load
to full load.
± 2% load regulation option is
available

Load Crest Factor

Maximum 2.5 at 90% load

Output Noise

High frequency ripple is less
than 500mVrms (20MHz BW)

Output Overload Protection

Current limiting with short circuit
protection.
Thermal shutdown with automatic
recovery in case of insufficient
cooling

Output Overvoltage Protection

140Vac (for 115Vac output) or
280Vac (for 230Vac output) by
internal supply voltage limiting

Efficiency

Depends on input and output
voltage combination.
Typically 78% at full load

Operating Temperature Range

0° C to +50° C for full specification
without derating.
Extended temperature ranges
available

Temperature Drift

0.05% per °C over operating
temperature range

Cooling

Built-in fans draw air into
the unit

Environmental Protection

Basic ruggedizing
Full ruggedizing and conformal
coating as option

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 - 95% non-condensing

MTBF

Min. 90,000 hours at 45°C
Demonstrated MTBF is
significantly higher
Fans excluded

Indicators

None

Control Input

None
Remote shutdown as option

Alarm Output

None
Option: output fail alarm (Form C)

Package/Dimensions (H x W x D)

Package size varies from
3U x 9.6" x 16" + 3U x 7.4" x 16"
(2 boxes) with modular configuration to a
3U x 19" x 16" (3U7 one box chassis)
Chassis-mount and 19" rack-mount
versions are available at the same price
for the 3U7 package.

Weight

14 kg (30 lb) approx.,

Connections

Input: terminal block
Output: standard AC receptacle
Option: compression type terminal block

RoHS Compliance

Fully compliant

Warranty

Two years subject to application
within good engineering practice

Enhancements to these general specifications can be accommodated upon request. Specifications are subject to change

Designer and manufacturer of quality ac-dc power supplies and battery chargers, converters, inverters, dc-output UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-proved Facility.



ABOPULSE ELECTRONICS LTD

110 Walgreen Road
Ottawa, Ontario. K0A 1L0. CANADA
Tel: +1-613-836-3511 Fax: +1-613-836-7488
E-mail: absopulse@absopulse.com
<http://www.absopulse.com>